

SPECIAL TRANSPORTER





These Generating Sets from 5 to 20kVA, are special preparations for vans and truks.

They are manufactured with a Kohler diesel engine, water cooled, electric 12V starting.

Coupling with a super-compact generator 400V 3-phases+N or 230V 1-phase - 50 Hz. Manual control panel with remote start from inside the truck. Electric distribution panel with ECC sockets available separately.

These generating sets are supplied without fuel tank, without battery and with separate muffler and electric panel.

Generating s	et			
Prime power	[KVA]	20		
Prime power	[KW]	16		
Stand-by power	[KVA]	22		
Stand-by power	[KW]	17,6		
Voltage	[V]	400 / 230		
Frequency	[Hz]	50		
Cosφ		0,8		
RPM	[rpm]	1500		
Starting	Electric	Electric with battery		
Generating set noise level at 7mt	dB(A)	73		



The image is only for demonstration purposes

Dimensions and weight

Lenght	[mm]	1500
Width	[mm]	600
Height	[mm]	800
Weight	[kg]	470



Engine				Alternator
Manufacturer		KOHLER	Manufacturer	SINCRO or similar
Model		LDW 2204	Poles number	4
Cooling system		Water	Phases number	3
Power	[Hp/kW]	26,5/19,5	Regulation	AVR
Nr. Of cylinders		4	Туре	Brushless
Displacement	[cm³]	2199	Overload accepted	10,00%
Consumtion ¾ load	[L/h]	4,5	Voltage accuracy	±1%
Engine oil capacity	[L]	4,5		

EQUIPMENTS

	Standard equipment	Optionals		
diesel	Diesel engine		Soundproof stainless steel canopy painted at 2 components	
	Triple-phase alternator	THEFT		
Tool State	First oil filling			
	Soundproof canopy painted at 2 components			
	Vibration dampers			
· · · · · · · · · · · · · · · · · · ·	Electric manual separated panel with remote start from inside the truck			



Greenpower AB Helsingborgsvägen Varalöv 262 96 Ängelholm Tel: 0431-222 40 E-mail: info@greenpower.se web:www.greenpower.se