






# 170F

AGG. 11/20

3~ 50 Hz. 400V	
<b>FPT INDUSTRIAL</b>	
EU STAGE 0	
69 dB(A) @ 7 mt	
250 lt	

PRIME POWER		STAND-BY POWER	
kVA	kW	kVA	kW
<b>170</b>	<b>136</b>	<b>187</b>	<b>149,6</b>

ENVIRONMENTAL CONDITIONS	
Temperature	<b>40° C</b>
Height	<b>1000 mslm</b>
Humidity	<b>60%</b>

**OPEN VERSION B200**
**SOUNDPROOF VERSION C200**


The image is only for demonstration purposes

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
<b>1670</b>	<b>2400</b>	<b>1100</b>	<b>2000</b>

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
<b>2000</b>	<b>3200</b>	<b>1100</b>	<b>2090</b>

## TECHNICAL DETAILS

<b>ELECTRICAL DATA</b>	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	PRP Ampere rating	245,4	A
<b>ENGINE</b>	Engine	FPT NEF N67TM4	
	Engine emissions standard (REG. UE 2016/1628)	EU STAGE 0	
	RPM governor	Mechanical	
	Performance class (ISO8528-5)	G2	
	Rpm	1500	rpm
	Nr. of cylinders	6	
	Bore x stroke	104 x 132	mm
	Displacement	6700	cc
	Induction system	Turbocharged	
	Cooling system	Water	
	Engine net prime power	200 (149)	Hp (kW)
	Exhaust gas aftertreatment	/	
<b>CONSUMPTION</b>	Fuel type	Diesel	
	Consumption @ 50-75-100% load	18 – 28 – 36,6	lt/h
	Standard tank capacity	250	lt
	Autonomy @ 75% load	8,9	h
<b>ALTERNATOR</b>	Alternator	STAMFORD – MECC ALTE – MARELLI MOTORI	
	Type	Self excited, brushless	
	Number of poles	4	
	Insulation class	H	
	Temperature rise class	H	
	Voltage regulation	AVR	
	Voltage precision	± 1	%
<b>GENERAL</b>	Sound level (soundproof version)	69	dB(A) 7mt
	Exhaust pipe diameter	114	mm
	Electrical system voltage	12	V

## ELECTRIC PANEL

MANUAL

AUTOMATIC MAINS FAILURE



<i>Electronic control unit with multimeter</i>	<b>COMAP IntelliLite 9</b>	<b>COMAP IntelliLite 9</b>
<i>Electrical panel enclosure protection degree</i>	<b>IP44</b>	
<i>ON-OFF electric panel switch</i>	<i>Key type</i>	<i>Without key</i>
<i>Emergency pushbutton</i>	<b>STANDARD</b>	
<i>Battery charge maintainer</i>	<i>/</i>	<b>12V 5A</b>
<i>Power supply</i>	<i>Full power terminal</i>	<i>Full power terminal</i>
<i>Circuit breaker</i>	<i>Magnetothermal type 4P ABB Tmax-T 320A</i>	<i>Magnetothermal type 4P ABB Tmax-T 320A</i>
<i>Main protection alarms</i>	<i>Min-max V and Hz. LOP. HWT. Battery charger alternator failure. Low fuel level</i>	

## STANDARD ELECTRONIC CONTROL UNIT

COMAP  
IntelliLite 9



*Functions: automatic or manual start, remote start, periodic test*

*Multimeter V (L1, L2, L3, N), A (L1, L2, L3), Hz, kVA, battery V, hour counter*

*Backlit LCD display. USB port*

*Communication accessories available: Ethernet, GSM-GPRS, 4G, GPS*

## OPTIONAL ELECTRONIC CONTROL UNIT




DEEP SEA DSE4520 MKII  
DEEP SEA DSE7320 MKII





COMAP AMF25

## SOUNDPROOF AND WEATHERPROOF CANOPY



<i>Self-supporting frame material</i>	<i>Carbon steel sheet, electro-welded, minimum thickness 3 mm</i>
<i>Soundproof canopy material</i>	<i>Carbon steel sheet, electro-welded, thickness between 1,5 and 4,5 mm</i>
<i>Painting</i>	<i>Epoxy powder RAL5015 textured, outdoor-proof</i>
<i>In-built fuel tank</i>	<b>250 lt + Drip tray</b>
<i>Soundproofing coating material</i>	<i>Polyester fiber. Fire resistance EN13501-1 class B</i>
<i>Muffler</i>	<i>In-built the canopy. Residential type with sound reduction 35 dB(A)</i>
<i>Access openings</i>	<i>n.3 doors with padlockable key lock</i>
<i>Electric panel</i>	<i>Lateral side position. Dedicated door with padlockable key lock</i>
<i>Fresh air intake and hot air expulsion</i>	
<i>Lifting system</i>	<i>n.2 lifting hooks</i>
<i>Support feet</i>	<i>n.4 support feet with holes for machine ground fastening</i>

## CONTAINER TRANSPORTABILITY ADVANTAGES

VERSION		20' BOX	40' BOX	40' HC
	N. transportable pieces	4	10	10
		2	6	6

## MAIN OPTIONS



*400A automatic transfer switch (ATS)*



*400 lt bigger fuel tank with drip tray*



*1000W engine preheating system*



*Electronic engine speed governor*



*Automatic fuel transfer kit with manual by-pass system*



*Residual current protection relay adjustable in sensitivity and intervention time*

## OTHER OPTIONS

*Power distribution socket set*

*Synchronizing electric panel*

*Battery switch*

*Remote control systems*

**ETHERNET, 2G - 3G - 4G, GPS**

*Further alternator brand*

*Quick couplings for connecting an external tank with three way valve*

*Outdoor, underground and transportable tanks*

*Slow or fast towing trailer*

*Front hot air expulsion canopy*

*Further colors*

## VERSIONS WITH SPECIAL EQUIPMENT



### RENTAL

*Special version with features designed for the rental market*



### ZERO NOISE

*Super sound-proofed special version, noise level 50, 55 or 60 dB(A)*

**Greenpower AB**  
 Helsingborgsvägen Varalöv,  
 262 96 Ängelholm, Sweden  
 Phone: +46 43122240  
 Email: [info@greenpower.se](mailto:info@greenpower.se)  
 Web: [www.greenpower.se](http://www.greenpower.se)