

# PhormiTex 66 (B)

Sun shading/Energy saving screen, B versions for hanging systems

## Technical data sheet

### Product description

<b>Type of product</b>	Woven Fabric	<b>Application</b>	Indoor
<b>Colour</b>	Aluminum/Diffuse; (B) w/ reinforced strips every 20 cm	<b>Material</b>	Alu/Modacryl/HDPE

### Properties

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	86 g/m <sup>2</sup>	±8,6 g/m <sup>2</sup>
Length		As required	-
Roll Width		335(B) - 400(B) cm	±2 cm
		131,9(B) - 157,5(B) in	±0,8 in
Mechanical Properties	Standard	Performance	
Energy saving	Phormium test method	60 %	
Direct Light transmission	Phormium test method	35 %	
Shading	Phormium test method	65 %	
Shrinkage	2h at 70°C	≤1 %	
Durability	Standard	Performance	
UV Stabilization	Phormium test method	600 kLy	
	DIN 4102	B1	
	NTA 8825	Class 1	
	ASTM E 84		
Flame retardant	NFPA 701 - 2015 Test Method 2		

#### Postadress:

TRÄDGÅRDSTEKNIK AB  
Helsingborgsvägen 578, Varalöv  
262 96 ÄNGELHOLM

Telefon : 0431-222 90  
Bg.nr : 5743-7980  
Org.nr : 556409-6120

#### URL:

[www.tradgardsteknik.se](http://www.tradgardsteknik.se)  
E-postadress:  
[info@tradgardsteknik.se](mailto:info@tradgardsteknik.se)