

GPC13000E



GPC13000E Professional series gasoline generating sets, 3000 rpm, sturdy and easy to handle, specially designed for professionals and yards. These generatng sets could be adopted easily in every situaton like houses, campings, hobby, yards . 3000 rpm gensets have been designed for stand-by use only. Not recommended using for more than 6 hours continuously or more than 500 hours/years.



PRIME POWER		STAND-BY POWER	
KVA	KW	KVA	KW
12	10,8	13,2	11,8

WEIGHT	DIMENSIONS		
kg	L [mm]	W [mm]	H [mm]
125	910	580	640

All data can be found out in the original technical datasheet of the engine and the alternator. Values shown are nominal values, they can change in every moment and without warning.

TECHNICAL DETAILS

ELECTRICAL DATA	Electrical system type	1F+N	~
	Power factor	0,9	φ
	Voltage	230	V
	Frequency	50	Hz
	Ampere rating	58	A
ENGINE DATA	Engine	HONDAGX630	
	Engine emissions	STAGE V	
	Standards Engine power	18 (13,2) Hp (kW)	
	Rpm	3000	
	Nr. of cylinders	2	
	Engine starting system	Electric start	
	Displacement	570	cc
FUEL CONSUMPTION DATA	Fuel type	Petrol	
	Consumption	4,3 lt/h @ 75%	
	Tank capacity	15liter	
	Autonomy	3,5 h	
ALTERNATOR DATA	Alternator	LINZELECTRIC – NSM	
	Type	Self-excited, with brushes	
	Voltage regulation	AVR	
	Voltage precision	± 5	%

All data can be found out in the original technical datasheet of the engine and the alternator. Values shown are nominal values, they can change in every moment and without warning.

STANDARD EQUIPMENT



Steel base frame, epoxy powder painted



autonomy Ant-vibration dampers



First filling liquids



Electric manual panel with multimeter and hour counter:

-n.1 schuko and n.1 230V 16A 5P + n.1 400V 16A 5P

EEC sockets

-12VDC socket. MCB with residual current protection



Greenpower AB

Helsingborgsvägen Varalöv

262 96 Ängelholm

Tel: 0431-222 40

E-mail: info@greenpower.se

web: www.greenpower.se