


## TECHNICAL DATA SHEET

# GP33 TR/S

### STRUCTURE



*Gear Box/alternator monoblock unit coupled through shaft, installed on a welded, powder-painted carbon steel base frame with demountable legs. (images are for illustrative purpose only)*

#### ELECTRIC PANEL

Magnetothermic circuit breaker
Earth fault device
63A 400V Socket
16A 230V Socket
E31 digital module:
- Voltmeter
- Frequency meter
- Hour counter

### TECHNICAL DATA

EQUIPMENT SPECIFICATION (ISO 8528/1)	50Hz
Prime power at cos $\phi$ 0.8	<b>30 kVA</b>
Prime power at cos $\phi$ 0.8	<b>24 kW</b>
Voltage available to the terminals	<b>400/230 V</b>
Dimensions (mm)	<b>855x580x985</b>
Weight (Kg)	<b>217</b>

GEAR BOX	50Hz
Brand and model	<b>6015.361.035</b>
R.P.M.	<b>1500</b>

ALTERNATOR	50Hz
Brand and model	<b>MECC ALTE ECP28-VL/4 (*)</b>
Synchronous with electronic governor voltage	<b><math>\pm 1\%</math></b>
Pole	<b>4</b>
Stator/rotator insulation	<b>H</b>
Protection level	<b>IP23</b>
Continuous power	<b>30 kVA</b>

(\*) = or similar brand



**Greenpower AB**

Helsingborgsvägen Varalöv

262 96 Ängelholm

Tel: 0431 222 40

E mail: info@greenpower.se

web:www.greenpower.se